



FEATURES

- · Wideband audio
- · Noise-cancelling microphone
- DSP-assisted echo cancellation
- Bendable boom arm with 270° rotation
- Acoustic shock protection
- Touch call control on ear cup
- · Mute light in boom arm tip
- Single connectivity: USB interface
- 4 headsets conference on single base



TECHNICAL SPECIFICATIONS

GENERAL

- Connection to PC via USB interface
- · Headset weight: 75g
- Wearing style: on-ear dual-sided
- · Talk time in wideband mode: up to 6 hours
- Talk time in narrowband mode: up to 8 hours
- Standby time: 100 hours

MICROPHONE

- Noise-cancelling
- Frequency range: 100 7,000 Hz

RECEIVER

- Frequency range: 100 20,000 Hz
- · Sound pressure: limited by acoustic shock protection

MECHANICAL

- Plastic covered metal headband, 5 mm wide
- Plastic boom arm
- · Foam ear cushion
- Magnetic charger pull

TECHNICAL

- DECT bands supported: EU, US, Latin America, South America
- · Automatic power adjustment: yes
- Wideband audio: BV32 + G722 codec
- Range, outdoor: 300 m
- Range, indoor: 60 m
- Full DECT security

PACKAGING

- Packaging type: brown box
- · Master carton contents: 10 units

ACCESSORIES

• Foam ear pads

BOX CONTENTS

- 1 x Headset (RTX7232)
- 1 x Base station (RTX7441)
- USB cable
- DC adaptor
- Safety sheet